

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation** Epoxy curing agent
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
RockSolid Floors Industrial
2271 2nd St N
North St Paul, MN 55109
Phone: 866-765-4310
Fax: 763-780-4896
- **1.4 Emergency telephone number:**
CHEMTREC
1-800-424-9300 (US/Canada)
+01 703-527-3887 (International)



2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.
The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.



H361: Suspected of damaging fertility or the unborn child.



GHS08 health hazard

Repr. 2 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



C; Corrosive

R34: Causes burns.



Xn; Harmful

R20/21/22-62-63: Harmful by inhalation, in contact with skin and if swallowed. Possible risk of impaired fertility. Possible risk of harm to the unborn child.



Xn; Sensitising

R42/43: May cause sensitisation by inhalation and skin contact.



Xi; Irritant

R37: Irritating to respiratory system.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS05 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Methyleneoxide, polymer with benzeamine, hydrogenated

Polyamido Amine

nonylphenol

2,4,6-tris(dimethylaminomethyl)phenol

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 2)

· **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H361.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P281 Use personal protective equipment as required.

P264 Wash thoroughly after handling.

P260 Do not breathe mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· **Additional information:** N/A

· **Hazard description:**

· **WHMIS-symbols:**

D1B - Toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects

E - Corrosive material



· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



* - Indicates a long term health hazard from repeated or prolonged exposures.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 3)

· HMIS Long Term Health Hazard Substances

25154-52-3 | nonylphenol

· 2.3 Other hazards

· Results of PBT and vPvB assessment






















- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 6811-71-9	Polyamido Amine  	25-50%
CAS: 135108-88-2	Methyleneoxide, polymer with benzeamine, hydrogenated   	25-50%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0	2,4,6-tris(dimethylaminomethyl)phenol  	<25%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5	Benzyl alcohol  	<15%
CAS: 112-57-2 EINECS: 203-986-2 Index number: 612-060-00-0	3,6,9-triazaundecamethylenediamine    	<10%
CAS: 25154-52-3 EINECS: 246-672-0 Index number: 601-053-00-8	nonylphenol  Repr. Cat. 3    	<10%
CAS: 1760-24-3 EINECS: 217-164-6	N-(3-(trimethoxysilyl)propyl)ethylenediamine   	<10%

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 4)

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Allergic reactions

Gastric or intestinal disorders

Dizziness

Coughing

· **Hazards**

Danger of gastric perforation.

Danger of pulmonary oedema.

Danger of convulsion.

Condition may deteriorate with alcohol consumption.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Firefighting measures

· **5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons unsuitable extinguishing agents:** None.

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 5)

- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Do not store together with oxidizing and acidic materials.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Store receptacle in a well ventilated area.
Keep container tightly sealed.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 6)

- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

100-51-6 Benzyl alcohol

WEEL (USA) | 10 ppm

112-57-2 3,6,9-triazaundecamethylenediamine

WEEL (USA) | 5 mg/m³
Skin; DSEN

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.
Use suitable respiratory protective device when aerosol or mist is formed.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 7)

- **Eye protection:**
Contact lenses should not be worn.



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No further relevant information available.
- **Risk management measures**
See Section 7 for additional information.
No further relevant information available.

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Viscous
· Colour:	Amber coloured
· Odour:	Amine-like
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	>392 °F / >200 °C

· **Flash point:** 262 °F / 130 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 698 °F / 370 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not self-igniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

· Lower:	1,3 Vol %
· Upper:	13,0 Vol %

· **Vapour pressure at 20 °C:** 0,1 hPa

· **Density at 20 °C:** 1 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 8)

· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	Not determined.
Solids content:	Not determined.
· 9.2 Other information	No further relevant information available.

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Reacts with catalysts.
Exothermic polymerization.
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid** Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Aldehyde
Carbon monoxide and carbon dioxide
Nitrogen oxides
Ammonia

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

112-57-2 3,6,9-triazaundecamethylenediamine

Dermal	LD50	660 mg/kg (rabbit)
--------	------	--------------------

25154-52-3 nonylphenol

Oral	LD50	1620 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 9)

- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Sensitisation:** Sensitization possible by inhalation and/or dermal contact.
- **Repeated dose toxicity:**
May cause damage to organs through prolonged or repeated exposure .
Repeated exposures may result in skin and/or respiratory sensitivity.

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** The material is harmful to the environment.
- **12.2 Persistence and degradability** The product is partly biodegradable. Significant residuals remain.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:**
Toxic for fish
Due to mechanical actions of the product (e.g. agglutinations) damages may occur.
The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.
- **Additional ecological information:**
- **General notes:**
This statement was deduced from the properties of the single components.
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
The product should not be released into the aquatic environment without preliminary treatments (purification plant).
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Must not reach sewage water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 10)

13 Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- **14.1 UN-Number**

- **DOT, ADR, IMDG, IATA**

UN2735

- **14.2 UN proper shipping name**

- **DOT, IATA**

POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(TETRAETHYLENEPENTAMINE, Methyleneoxide,
polymer with benzeamine, hydrogenated)

- **ADR**

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(TETRAETHYLENEPENTAMINE, Methyleneoxide,
polymer with benzeamine, hydrogenated),
ENVIRONMENTALLY HAZARDOUS

- **IMDG**

POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(TETRAETHYLENEPENTAMINE, Methyleneoxide,
polymer with benzeamine, hydrogenated), MARINE
POLLUTANT

- **14.3 Transport hazard class(es)**

- **DOT**



- **Class**

8 Corrosive substances.

- **Label**

8

- **ADR**



- **Class**

8 (C7) Corrosive substances.

(Contd. on page 12)

Safety Data Sheet



according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 11)

· Label	8
· IMDG	
	
· Class	8 Corrosive substances.
· Label	8
· IATA	
	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· DOT, ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S. (TETRAETHYLENEPENTAMINE, Methyleneoxide, polymer with benzeamine, hydrogenated), ENVIRONMENTALLY HAZARDOUS, 8, II

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 12)

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Canada**

- **Canadian Domestic Substances List (DSL)**

135108-88-2 Methyleneoxide, polymer with benzeamine, hydrogenated

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

100-51-6 Benzyl alcohol

112-57-2 3,6,9-triazaundecamethylenediamine

25154-52-3 nonylphenol

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 13)

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

100-51-6	Benzyl alcohol
112-57-2	3,6,9-triazaundecamethylenediamine
25154-52-3	nonylphenol

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
R20/21	Harmful by inhalation and in contact with skin.
R20/22	Harmful by inhalation and if swallowed.
R21/22	Harmful in contact with skin and if swallowed.
R22	Harmful if swallowed.
R34	Causes burns.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.
R63	Possible risk of harm to the unborn child.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 ACGIH: American Conference of Governmental Industrial Hygienists
 NFPA: National Fire Protection Association (USA)

(Contd. on page 15)

Safety Data Sheet
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 01.03.2013

Revision: 01.03.2013

Trade name: RockSolid Industrial Moisture Stopping Primer Kit Part B

(Contd. of page 14)

HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com