

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

## 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: RockSolid Industrial Polycuramine Part A**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the preparation** Polycuramine Resin
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
ROCKSOLID FLOORS INDUSTRIAL  
2271 2nd St N  
North St Paul, MN 55109  
Phone: 866-765-4310 Fax:  
763-780-4896
- **1.4 Emergency telephone number:**  
CHEMTREC  
1-800-424-9300 (US/Canada)  
+01 703-527-3887 (International)



## 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.



GHS08 health hazard

Muta. 2                      H341 Suspected of causing genetic defects.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2                      H315 Causes skin irritation.

Eye Irrit. 2                      H319 Causes serious eye irritation.

Skin Sens. 1                      H317 May cause an allergic skin reaction.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R46:                      May cause heritable genetic damage.



Xi; Irritant

R36/38:                      Irritating to eyes and skin.

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013


Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 1)

 Xi; Sensitising

R43: May cause sensitisation by skin contact.

 N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

• **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

• **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.

The product is classified and labelled according to the CLP regulation.

• **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS07 GHS08 GHS09

• **Signal word** Warning

• **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq 700$ )

Reaction products of Epichlorohydrin and Bisphenol A

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

• **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H411.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

• **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

(Contd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 2)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P281 Use personal protective equipment as required.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.

· **Additional information:**

Contains epoxy constituents. May produce an allergic reaction.  
 Restricted to professional users.  
 Keep out of the reach of children

· **Hazard description:**

· **WHMIS-symbols:**

D2A - Very toxic material causing other toxic effects



· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



\* - Indicates a long term health hazard from repeated or prolonged exposures.

· **HMIS Long Term Health Hazard Substances**

25085-99-8	Reaction products of Epichlorohydrin and Bisphenol A
100-41-4	ethylbenzene

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

(Contd. on page 4)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

		(Contd. of page 3)
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) Xi R36/38; Xi R43; N R51/53 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	50-100%
CAS: 25085-99-8	Reaction products of Epichlorohydrin and Bisphenol A T Muta. Cat. 3 R46; Xi R38; Xi R43; N R51 Muta. 2, H341 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1A, H317	10-25%
	Trade Secret Xi R38; Xi R43 Skin Irrit. 2, H315; Skin Sens. 1, H317	10-25%
	Trade Secret Xi R36/37/38 R10 Flam. Liq. 3, H226 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<10%
CAS: 17557-23-2 EINECS: 241-536-7 Index number: 603-094-00-7	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane Xi R38; Xi R43 Skin Irrit. 2, H315; Skin Sens. 1, H317	<10%
<ul style="list-style-type: none"> <li>· <b>Additional information:</b> For the wording of the listed risk phrases refer to section 16.</li> </ul>		
<ul style="list-style-type: none"> <li>· <b>Notable Trace Components (&lt; 0.1% w/w)</b></li> </ul>		
CAS: 122-60-1 EINECS: 204-557-2 Index number: 603-067-00-X	phenyl glycidyl ether T Carc. Cat. 2 R45; Xn R20-68; Xi R37/38; Xi R43 R52/53 Muta. Cat. 3 Muta. 2, H341; Carc. 1B, H350 Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Chronic 3, H412	
CAS: 106-89-8 EINECS: 203-439-8 Index number: 603-026-00-6	1-chloro-2,3-epoxypropane T Carc. Cat. 2 R45-23/24/25; C R34; Xi R43 R10 Flam. Liq. 3, H226 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 Carc. 1B, H350 Skin Corr. 1B, H314 Skin Sens. 1, H317	
CAS: 2238-07-5 EINECS: 218-802-6	2,2'-[oxybis(methylene)]bisoxirane Xn R22 Acute Tox. 4, H302	

(Contd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 4)

## 4 First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
In case of irregular breathing or respiratory arrest provide artificial respiration.  
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:**  
Remove contact lenses if worn.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
Nausea  
Cramp  
Dizziness  
Headache  
Allergic reactions
- **Hazards** Danger of disturbed cardiac rhythm.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
Monitor circulation, possible shock treatment.  
If necessary oxygen respiration treatment.  
Medical supervision for at least 48 hours.  
Later observation for pneumonia and pulmonary oedema.  
In cases of irritation to the lungs, initial treatment with corticosteroid inhalants.  
Treat skin and mucous membrane with antihistamine and corticoid preparations.

## 5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Foam  
Alcohol resistant foam  
Fire-extinguishing powder  
Carbon dioxide  
Gaseous extinguishing agents  
Water haze or fog
- **For safety reasons unsuitable extinguishing agents:** None.
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.

(Contd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

Wear fully protective suit.

- **Additional information** Cool endangered receptacles with water spray.

(Contd. of page 5)

## 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- **7.1 Precautions for safe handling**

Avoid splashes or spray in enclosed areas.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about fire - and explosion protection:** Keep respiratory protective device available.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Protect from humidity and water.

- **Information about storage in one common storage facility:**

Store away from oxidizing agents.

Do not store together with acids.

Store away from foodstuffs.

- **Further information about storage conditions:**

Store under lock and key and out of the reach of children.

Keep container tightly sealed.

- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

<b>Trade name: RockSolid Industrial Polycuramine Part A</b>
---

(Contd. of page 6)

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

<b>106-89-8 1-chloro-2,3-epoxypropane (&lt;0,1%)</b>
--

PEL (USA)	Long-term value: 19 mg/m <sup>3</sup> , 5 ppm Skin
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 1,9 mg/m <sup>3</sup> , 0,5 ppm Skin
EL (Canada)	Long-term value: 0,1 ppm Skin; IARC 2A, R
EV (Canada)	Long-term value: 0,5 ppm Skin

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Filter AX

Use suitable respiratory protective device when high concentrations are present.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

(Contd. on page 8)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 7)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR

Neoprene gloves

Nitrile rubber, NBR

- **Eye protection:**

Goggles recommended during refilling



Safety glasses

- **Body protection:** Impervious protective clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

## 9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Liquid

**Colour:** Whitish

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not self-igniting.

(Contd. on page 9)



# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 8)

· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC (US EPA Method 24)</b>	4,0 % Wt
· <b>9.2 Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Toxic fumes may be released if heated above the decomposition point.  
Reacts with strong acids.  
Exothermic polymerization.  
Reacts with catalysts.  
Reacts with peroxides.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Halogenated hydrocarbons  
Hydrogen fluoride  
Nitrogen oxides  
Carbon monoxide and carbon dioxide

(Contd. on page 10)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 9)

## 11 Toxicological information

- **11.1 Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

**1330-20-7 xylene**

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

**100-41-4 ethylbenzene**

Oral LD50 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rabbit)

**106-89-8 1-chloro-2,3-epoxypropane**

Oral LD50 90 mg/kg (rat)

Dermal LD50 515 mg/kg (rabbit)

Inhalative LC50/4 h 250 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:**

Sensitizing effect through inhalation is possible by prolonged exposure.

Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Danger through skin adsorption.

Carcinogenic.

Toxic and/or corrosive effects may be delayed up to 24 hours.

- **Sensitisation:** Sensitization possible by skin contact.

- **Repeated dose toxicity:**

May cause damage to organs through prolonged or repeated exposure .

Repeated exposures may result in skin and/or respiratory sensitivity.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**

Muta. 2

## 12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:** Toxic for aquatic organisms

- **12.2 Persistence and degradability** The product is partially biodegradable. Significant residuals remain.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 11)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 10)

- **Additional ecological information:**
- **General notes:**  
This statement was deduced from the properties of the single components.  
Avoid transfer into the environment.  
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | <p style="margin: 0;">N/A<br/>UN3082</p>   |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul> | <p style="margin: 0;">N/A<br/>3082 ENVIRONMENTALLY HAZARDOUS<br/>SUBSTANCE, LIQUID, N.O.S. (Mixed Epoxy Resin)<br/>ENVIRONMENTALLY HAZARDOUS SUBSTANCE,<br/>LIQUID, N.O.S. (Mixed Epoxy Resin), MARINE<br/>POLLUTANT<br/>ENVIRONMENTALLY HAZARDOUS SUBSTANCE,<br/>LIQUID, N.O.S. (Mixed Epoxy Resin)</p> |

(Contd. on page 12)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS



Printing date 17.07.2013

Revision: 17.07.2013

<b>Trade name: RockSolid Industrial Polycuramine Part A</b>
---

(Contd. of page 11)

<b>· 14.3 Transport hazard class(es)</b>	
<b>· DOT</b>	
<b>· Class</b>	N/A
<hr/>	
<b>· ADR</b>	
	
<b>· Class</b>	9 (M6) Miscellaneous dangerous substances and articles.
<b>· Label</b>	9
<hr/>	
<b>· IMDG, IATA</b>	
	
<b>· Class</b>	9 Miscellaneous dangerous substances and articles.
<b>· Label</b>	9
<hr/>	
<b>· 14.4 Packing group</b>	
<b>· DOT</b>	N/A
<b>· ADR, IMDG, IATA</b>	III
<hr/>	
<b>· 14.5 Environmental hazards:</b>	
<b>· Marine pollutant:</b>	Yes
	Symbol (fish and tree)
<b>· Special marking (ADR):</b>	Symbol (fish and tree)
<b>· Special marking (IATA):</b>	Symbol (fish and tree)
<hr/>	
<b>· 14.6 Special precautions for user</b>	Warning: Miscellaneous dangerous substances and articles.
<b>· Danger code (Kemler):</b>	90
<b>· EMS Number:</b>	F-A,S-F
<hr/>	
<b>· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
<hr/>	
<b>· Transport/Additional information:</b>	
<hr/>	
<b>· ADR</b>	
<b>· Limited quantities (LQ)</b>	5L
<b>· Transport category</b>	3
<b>· Tunnel restriction code</b>	E



(Contd. on page 13)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Industrial Polycuramine Part A

(Contd. of page 12)

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul> | UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Reaction products of Epichlorohydrin and Bisphenol A), 9, III |
|---|--|

## 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

Present in trace quantities: 122-60-1, 106-89-8.

100-41-4 ethylbenzene

122-60-1 phenyl glycidyl ether

106-89-8 1-chloro-2,3-epoxypropane

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

122-60-1 phenyl glycidyl ether

2238-07-5 2,2'-[oxybis(methylene)]bisoxirane

106-89-8 1-chloro-2,3-epoxypropane

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

- **IARC (International Agency for Research on Cancer)**

106-89-8 1-chloro-2,3-epoxypropane

2A

122-60-1 phenyl glycidyl ether

2A

(Contd. on page 14)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 13)

100-41-4	ethylbenzene	2B
· <b>TLV (Threshold Limit Value established by ACGIH)</b>		
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
122-60-1	phenyl glycidyl ether	A3
2238-07-5	2,2'-[oxybis(methylene)]bisoxirane	A4
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
122-60-1	phenyl glycidyl ether	
2238-07-5	2,2'-[oxybis(methylene)]bisoxirane	
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

· **Canada**· **Canadian Domestic Substances List (DSL)**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq 700$ )
25085-99-8	Reaction products of Epichlorohydrin and Bisphenol A
100-41-4	ethylbenzene
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs
98-56-6	4-chloro-alpha, alpha, alpha-trifluorotoluene
1330-20-7	xylene

· **Canadian Ingredient Disclosure list (limit 0.1%)**

100-41-4	ethylbenzene
----------	--------------

· **Canadian Ingredient Disclosure list (limit 1%)**

None of the ingredients is listed.

· **National regulations:**· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.

(Contd. on page 15)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 17.07.2013

Revision: 17.07.2013

**Trade name: RockSolid Industrial Polycuramine Part A**

(Contd. of page 14)

H411 Toxic to aquatic life with long lasting effects.  
 R10 Flammable.  
 R36/37/38 Irritating to eyes, respiratory system and skin.  
 R36/38 Irritating to eyes and skin.  
 R38 Irritating to skin.  
 R43 May cause sensitisation by skin contact.  
 R46 May cause heritable genetic damage.  
 R51 Toxic to aquatic organisms.  
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 WHMIS: Workplace Hazardous Materials Information System (Canada)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent

• **Sources**

SDS Prepared by:  
 ChemTel Inc.  
 1305 North Florida Avenue  
 Tampa, Florida USA 33602-2902  
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573  
 Website: [www.chemtelinc.com](http://www.chemtelinc.com)