Printing date 17.07.2013

Revision: 17.07.2013

1 Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
 Trade name: RockSolid Floors Industrial Polycuramine Part B 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
Application of the substance / the preparation Polycuramine Activator
 1.3 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: ROCKSOLID FLOORS INDUSTRIAL 2271 2nd St N North St Paul, MN 55109 Phone: 866-765-4310 Fax: 763-780-4896 The world's toughest coatings[*]
 • 1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (US/Canada) +01 703-527-3887 (International)
2 Hazards identification
 • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008 The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. GHS05 corrosion
Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Acute Tox. 4H302 Harmful if swallowed.Acute Tox. 4H312 Harmful in contact with skin.Skin Sens. 1H317 May cause an allergic skin reaction.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
• Classification according to Directive 67/548/EEC or Directive 1999/45/EC
C; Corrosive R35: Causes severe burns.
Xn; Harmful R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
Xi; Sensitising
R43: May cause sensitisation by skin contact.
(Contd. on page 2)

GHS

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

(Contd. of page 1) · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. · Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS05 GHS07 · Signal word Danger · Hazard-determining components of labelling: 3-aminomethyl-3,5,5-trimethylcyclohexylamine Polvetheramine trimethylhexane-1,6-diamine Benzyl alcohol · Hazard statements The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412. H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eve damage. May cause an allergic skin reaction. H317 Harmful to aquatic life with long lasting effects. H412 Precautionary statements P101 If medical advice is needed, have product container or label at hand. Keep out of reach of children. P102 Read label before use. P103 Wear protective gloves / eve protection. P280 Wash thoroughly after handling. P264 Do not breathe mist/vapours/spray. P260 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. · Hazard description: · WHMIS-symbols: D2B - Toxic material causing other toxic effects (Contd. on page 3)

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B (Contd. of page 2) E - Corrosive material · NFPA ratings (scale 0 - 4) Health = 3Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 3 Health = 3 FIRE • Fire = 0 **REACTIVITY** Reactivity = 0 · HMIS Long Term Health Hazard Substances 25154-52-3 nonylphenol · 2.3 Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · **vPvB:** Not applicable. **3 Composition/information on ingredients** · Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: CAS: 2855-13-2 3-aminomethyl-3 5 5-trimethylcyclohexylamine 25-50%

07.0. 2000-10-2	S-annioneury-5,5,5-unneurycyclonexylannie	23-3070
EINECS: 220-666-8	🛃 C R34; 🗙 Xn R21/22; 🔀 Xi R43	
Index number: 612-067-00-9	R52/53	
	 Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 Aquatic Chronic 3, H412 	
CAS: 9046-10-0	Polyetheramine	10-25%
	🔁 C R34; 🗙 Xn R21/22	
	R52/53	
	Skin Corr. 1B, H314	
	Acute Tox. 4, H302; Acute Tox. 4, H312	
	Aquatic Chronic 3, H412	
CAS: 100-51-6	Benzyl alcohol	10-25%
EINECS: 202-859-9	🗙 Xn R20/22	
Index number: 603-057-00-5	🕂 Acute Tox. 4, H302; Acute Tox. 4, H332	1
	(Conto	l. on page 4)

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

CAS: 98-54-4	4-tert-butylphenol	(Contd. of page <10%
EINECS: 202-679-0	Xi R37/38-41; 🙀 N R51/53	\$107
	Eye Dam. 1, H318	
	Aquatic Chronic 2, H411	
	🚯 Skin Irrit. 2, H315; STOT SE 3, H335	
	Trade Secret	<10%
	📑 C R34; 🗙 Xn R22; 🗙 Xi R43 R52/53	
	Skin Corr. 1B, H314	
	Acute Tox. 4, H302; Skin Sens. 1, H317	
	Aquatic Chronic 3, H412	
	Trade Secret	<10%
	🛃 C R34; 🙀 Xn R22	
	Skin Corr. 1B, H314	
	Acute Tox. 4, H302; Acute Tox. 4, H332	
	Trade Secret	<10%
	🙀 C R34; 🗙 Xn R22-62-63; 擬 N R50/53 Repr. Cat. 3	
	🚸 Repr. 2, H361fd	
	Skin Corr. 1B, H314	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Acute Tox. 4, H302	
· SVHC		

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

 4.1 Description of first aid measures 	
· General information:	
Immediately remove any clothing soiled by the product.	
Symptoms of poisoning may even occur after several hours; therefore medical observ	ation for at least 48
hours after the accident.	
· After inhalation:	
Supply fresh air; consult doctor in case of complaints.	
In case of unconsciousness place patient stably in side position for transportation.	
· After skin contact:	
Immediately wash with water and soap and rinse thoroughly.	
If skin irritation continues, consult a doctor.	
Seek immediate medical help for blistering or open wounds.	
· After eye contact:	
Remove contact lenses if worn, if possible.	
Rinse opened eye for several minutes under running water. Then consult a doctor.	
· After swallowing:	
Rinse out mouth and then drink plenty of water.	
Do not induce vomiting; call for medical help immediately.	
	(Contd. on page 5)

Printing date 17.07.2013

Revision: 17.07.2013

Printing date 17.07.2013

Revision: 17.07.2013

(Contd. of page 4) · 4.2 Most important symptoms and effects, both acute and delayed Cramp Nausea Dizziness Headache **Breathing difficulty** Allergic reactions · Hazards Danger of gastric perforation. Danger of impaired breathing. Condition may deteriorate with alcohol consumption. • 4.3 Indication of any immediate medical attention and special treatment needed May produce a corrosive effect. Medical supervision for at least 48 hours. If necessary oxygen respiration treatment. Monitor circulation, possible shock treatment.

5 Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Foam Alcohol resistant foam Gaseous extinguishing agents Carbon dioxide Water in floading quantities
- Water in flooding quantities.
- · For safety reasons unsuitable extinguishing agents: None.

Trade name: RockSolid Floors Industrial Polycuramine Part B

- \cdot 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

- Wear fully protective suit.
- · Additional information Cool endangered receptacles with water fog or haze.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
(Contd. on page 6)

Printing date 17.07.2013

Revision: 17.07.2013

(Contd. of page 5)

Trade name: RockSolid Floors Industrial Polycuramine Part B

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid splashes or spray in enclosed areas. · Information about fire - and explosion protection: No special measures required. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame. Protect from humidity and water. Unsuitable material for receptacle: aluminium. Unsuitable material for receptacle: steel. Information about storage in one common storage facility: Store away from oxidizing agents. Do not store together with acids. Store away from foodstuffs. Store away from metals. · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles. Store receptacle in a well ventilated area. Protect from humidity and water. · 7.3 Specific end use(s) No further relevant information available. 8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

100-51-6 Benzyl alcohol

WEEL (USA) Long-term value: 10 ppm

- 1477-55-0 m-phenylenebis(methylamine)
- REL (USA)
 Short-term value: C 0,1 mg/m³

 Skin
 Skin
- TLV (USA) Short-term value: C 0,1 mg/m³ Skin

(Contd. on page 7)

Printing date 17.07.2013

Revision: 17.07.2013

(Contd. on page 8)

Trade name: RockSolid Floors Industrial Polycuramine Part B

		(Contd. of page 6)
EL (Canada)	Short-term value: C 0,1 mg/m³ Skin	
EV (Canada)		
• DNELs No fur	rther relevant information available.	
• PNECs No fur	rther relevant information available.	
· Additional inf	formation: The lists valid during the making were used as basis.	
· 8.2 Exposure	controls	
	tective equipment:	
	ective and hygienic measures:	
	cautionary measures are to be adhered to when handling chemicals.	
	om foodstuffs, beverages and feed.	
	emove all soiled and contaminated clothing.	
	before breaks and at the end of work.	
	gases / fumes / aerosols.	
· Respiratory p	with the eyes and skin.	
	espiratory protective device in case of insufficient ventilation.	
	espiratory protective device when aerosol or mist is formed.	
	ved organic vapor respirator equipped with a dust/mist prefilter should be us	ed.
· Protection of		001
	ctive gloves	proporation
Selection of t degradation.	terial has to be impermeable and resistant to the product/ the substance/ the the glove material on consideration of the penetration times, rates of c	
 Material of gl 		
quality and v substances, th checked prior	of the suitable gloves does not only depend on the material, but also or varies from manufacturer to manufacturer. As the product is a prepa the resistance of the glove material can not be calculated in advance and has to the application.	ration of several
	ime of glove material	1
	ak through time has to be found out by the manufacturer of the protective g	poves and has to
be observed.	anent contact gloves made of the following materials are suitable:	
Butyl rubber, E	• •	
Neoprene glov		
Nitrile rubber,		
· Eye protectio		
	s should not be worn.	
Sofat	y glasses	
	y yiasses	
· Body protect	ion: Alkaline resistant protective clothing	
		(Contd. on page 8)

Printing date 17.07.2013

Revision: 17.07.2013

(Contd. of page 7)

Trade name: RockSolid Floors Industrial Polycuramine Part B

· Limitation and supervision of exposure into the environment

No further relevant information available. • Risk management measures See Section 7 for additional information. No further relevant information available.

• 9.1 Information on basic physical and chemical properties • General Information • Appearance: Form: Liquid Colour: Yellow • Odour: Amine-like • Odour threshold: Not determined. • pH-value: Not determined. • pH-value: Undetermined. • Flange in condition Undetermined. Boiling point/Melting range: Undetermined. • Flash point: Not applicable. • Flammability (solid, gaseous): Not determined.
Form:LiquidColour:Yellow• Odour:Amine-like• Odour threshold:Not determined.• pH-value:Not determined.• Change in condition Melting point/Melting range:Undetermined.• Change in condition Melting point/Boiling range:Undetermined.• Flash point:Not applicable.• Flammability (solid, gaseous):Not applicable.• Ignition temperature:Not determined.
Colour:Yellow· Odour:Amine-like· Odour threshold:Not determined.· pH-value:Not determined.· Change in condition Melting point/Melting range:Undetermined.· Change in condition Melting point/Boiling range:Undetermined.· Flash point:Not applicable.· Flammability (solid, gaseous):Not applicable.· Ignition temperature:Not determined.
· Odour: Amine-like · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Undetermined. Melting point/Melting range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
· Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
· Change in condition Undetermined. Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
Boiling point/Boiling range: Undetermined. · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
· Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Not determined.
• Flammability (solid, gaseous): Not applicable. • Ignition temperature: Not determined.
· Ignition temperature: Not determined.
December 2010 Participation of the second se
Decomposition temperature: Not determined.
Self-igniting: Product is not self-igniting.
Danger of explosion: Product does not present an explosion hazard.
· Explosion limits:
Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.
Density: Not determined.
· Relative density Not determined.
· Vapour density Not determined.
• Evaporation rate Not determined.
· Solubility in / Miscibility with
water: Slightly soluble.
· Partition coefficient (n-octanol/water): Not determined.
· Viscosity:
Dynamic: Not determined.
(Contd. on pa

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

		(Contd. of page 8)
Kinematic:	Not determined.	
Solvent content: Organic solvents:	Not determined.	
Solids content: · 9.2 Other information	Not determined. No further relevant information available.	

10 Stability and reactivity

· 10.1 Reactivity

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with certain metals.

Reacts with strong oxidizing agents.

Exothermic reaction with acids.

Develops corrosive gases/fumes.

Toxic fumes may be released if heated above the decomposition point.

Corrodes aluminium.

Corrodes copper and brass.

• 10.4 Conditions to avoid Keep away from heat and direct sunlight.

• **10.5 Incompatible materials:** No further relevant information available.

- 10.6 Hazardous decomposition products:
- Ammonia

Nitrogen oxides

Carbon monoxide and carbon dioxide

Acute to		on toxicological effects	
· LD/LC50	values r	elevant for classification:	
2855-13-	2 3-amin	omethyl-3,5,5-trimethylcyclohexylamine	
Oral	LD50	1030 mg/kg (rat)	
100-51-6	Benzyl a	Icohol	
Oral	LD50	1230 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
98-54-4 4	l-tert-but	ylphenol	
Oral	LD50	2951 mg/kg (rat)	
Dermal	LD50	2288 mg/kg (rabbit)	

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

25620-58-0 trimet	hylhexane-1,6-diamine
Oral LD50	900 mg/kg (rat)
1477-55-0 m-phe	nylenebis(methylamine)
Oral LD50	1040 mg/kg (rat)
Inhalative LC50/4	h 2,4 mg/l (rat)
25154-52-3 nonyl	phenol
Oral LD50	1620 mg/kg (rat)
· Primary irritant e	ffect:
	ng caustic effect on skin and mucous membranes.
· on the eye: Stron	g caustic effect.
· Sensitization: Se	nsitization possible through skin contact.
· Additional toxico	logical information:
Classification Guid	ws the following dangers according to the calculation method of the General E delines for Preparations as issued in the latest version:
Harmful Corrosive	
Irritant	
Danger through sk	cin adsorption
	ad to a strong caustic effect on mouth and throat and to the danger of perforation
esophagus and st	
coopriaguo anu su	omach.
Toxic and/or corro	omach. sive effects may be delayed up to 24 hours. nsitization possible by skin contact.
Toxic and/or corro	sive effects may be delayed up to 24 hours.
Toxic and/or corro	sive effects may be delayed up to 24 hours. nsitization possible by skin contact.
Toxic and/or corro • Sensitisation: Se • Repeated dose to	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity.
Toxic and/or corro • Sensitisation: Se • Repeated dose to	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity.
Toxic and/or corro • Sensitisation: Se • Repeated dose to 2 Ecological infe	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity.
Toxic and/or corro • Sensitisation: Se • Repeated dose to 2 Ecological info • 12.1 Toxicity	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity. ormation
Toxic and/or corro • Sensitisation: Se • Repeated dose to 2 Ecological info • 12.1 Toxicity • Aquatic toxicity:	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity. ormation The product contains materials that are harmful to the environment.
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. bxicity: Repeated exposures may result in skin and/or respiratory sensitivity. brmation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity. ormation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available.
Toxic and/or corro • Sensitisation: Se • Repeated dose to • Comparison • Compariso	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity. ormation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available.
Toxic and/or corro • Sensitisation: Se • Repeated dose to • Constant Se • Repeated dose to • Constant Se • Constant Sector • 12.1 Toxicity • Aquatic toxicity: • 12.2 Persistence • 12.3 Bioaccumula • 12.4 Mobility in s • Ecotoxical effect	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity. ormation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available.
Toxic and/or corro Sensitisation: Se Repeated dose to Certain Content of the sensitive Certain Certain Content of the sensitive Certain Certain	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. oxicity: Repeated exposures may result in skin and/or respiratory sensitivity. ormation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s:
Toxic and/or corro Sensitisation: Se Repeated dose to 2 Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Diricity: Repeated exposures may result in skin and/or respiratory sensitivity. Dirmation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s: I actions of the product (e.g. agglutinations) damages may occur.
Toxic and/or corro Sensitisation: Se Repeated dose to 2 Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Diricity: Repeated exposures may result in skin and/or respiratory sensitivity. Dirmation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s: I actions of the product (e.g. agglutinations) damages may occur. <i>r</i> gen-consuming. The declared action may be partly caused by lack of oxygen.
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Diricity: Repeated exposures may result in skin and/or respiratory sensitivity. Dirmation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s: I actions of the product (e.g. agglutinations) damages may occur. <i>r</i> gen-consuming. The declared action may be partly caused by lack of oxygen.
Toxic and/or corro Sensitisation: Se Repeated dose to 2 Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog General notes:	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Dormation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s: I actions of the product (e.g. agglutinations) damages may occur. rgen-consuming. The declared action may be partly caused by lack of oxygen. gical information:
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog General notes: This statement wa	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and for an and sensitity is a sense of the single components. Divicity: Repeated ex
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog General notes: This statement wa Avoid transfer into	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and respiratory sensitivity. Divicity: Repeated exposures may respiratory sensitivi
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog General notes: This statement wa Avoid transfer into	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and respiratory sensitivity. Divicity: Repeated exposures may respiratory sensitivi
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog General notes: This statement wa Avoid transfer into Due to available	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and respiratory sensitivity. Divicity: Repeated exposures may respiratory sensitivi
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 2 Ecological info • 12.1 Toxicity • Aquatic toxicity: • 12.2 Persistence • 12.3 Bioaccumula • 12.4 Mobility in s • Ecotoxical effect • Remark: Due to mechanical The product is oxy • Additional ecolog • General notes: This statement wa Avoid transfer into Due to available damage of the env	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Dirmation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s: I actions of the product (e.g. agglutinations) damages may occur. rgen-consuming. The declared action may be partly caused by lack of oxygen. gical information: Its deduced from the properties of the single components. the environment. data on eliminability/decomposition and bioaccumulation potential prolonged ter
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 2 Ecological info • 12.1 Toxicity • Aquatic toxicity: • 12.2 Persistence • 12.3 Bioaccumula • 12.4 Mobility in s • Ecotoxical effect • Remark: Due to mechanical The product is oxy • Additional ecolog • General notes: This statement wa Avoid transfer into Due to available damage of the env Water hazard clas	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Dirmation The product contains materials that are harmful to the environment. and degradability Not easily biodegradable ative potential No further relevant information available. oil No further relevant information available. s: I actions of the product (e.g. agglutinations) damages may occur. rgen-consuming. The declared action may be partly caused by lack of oxygen. gical information: Its deduced from the properties of the single components. the environment. data on eliminability/decomposition and bioaccumulation potential prolonged ter <i>i</i> ronment can not be excluded.
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanical The product is oxy Additional ecolog General notes: This statement wa Avoid transfer into Due to available damage of the env Water hazard class Do not allow production	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result in skin and/or respiratory sensitivity. Discity: Repeated exposures may result information available. Discity: Repeated exposure relevant information available. Discity: Repeated exposed exposed exposed by lack of oxygen. Discity: Repeated exposed exp
Toxic and/or corro Sensitisation: Se Repeated dose to Ecological info 12.1 Toxicity Aquatic toxicity: 12.2 Persistence 12.3 Bioaccumula 12.4 Mobility in s Ecotoxical effect Remark: Due to mechanica The product is oxy Additional ecolog General notes: This statement wa Avoid transfer into Due to available damage of the env Water hazard class Do not allow produce Must not reach se	sive effects may be delayed up to 24 hours. nsitization possible by skin contact. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures may result in skin and/or respiratory sensitivity. Divicity: Repeated exposures and the single components. Divicity: Repeated exposures and bioaccumulation potential prolonged tervironment can not be excluded. Divicity: S 2 (German Regulation) (Self-assessment): hazardous for water uct to reach ground water, water course or sewage system.

GHS

Printing date 17.07.2013

Revision: 17.07.2013

(Contd. of page 10)

Trade name: RockSolid Floors Industrial Polycuramine Part B

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Can be disposed of with household garbage with prior chemical-physical or biological treatment following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number			
· DOT, ADR, IMDG, IATA	UN2735		
· 14.2 UN proper shipping name			
·DOT	Polyamines, liquid, corrosive, n.o.s. (Polyetheramin Isophoronediamine)		
· ADR	2735 POLYAMINES, LIQUID, CORROSIVE, N.C (Polyetheramine, ISOPHORONEDIAMINE)		
· IMDG, IATA	POLYAMINES, LIQUID, CORROSIVE, N.O. (Polyetheramine, ISOPHORONEDIAMINE)		
· 14.3 Transport hazard class(es)			
· DOT			
Service 3			
· Class	8 Corrosive substances.		
· Label	8		

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

	(Contd. of page 1
· ADR	
A Contraction of the second se	
· Class	8 (C7) Corrosive substances.
· Label	8
· IMDG, IATA	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· DOT, ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
 Segregation groups 	Alkalis
· 14.7 Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
 Limited quantities (LQ) 	5L
Transport category	3
Tunnel restriction code	E
· UN "Model Regulation":	UN2735, POLYAMINES, LIQUID, CORROSIVI N.O.S. (Polyetheramine, ISOPHORONEDIAMINE), III

15 Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot United States (USA)

·SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 13)

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

Continue 242 (Constitution of amigal listing ways	(Contd. of page
Section 313 (Specific toxic chemical listings): None of the ingredients is listed.	
.	
• TSCA (Toxic Substances Control Act): All ingredients are listed.	
Proposition 65 (California):	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
 TLV (Threshold Limit Value established by ACGIH) 	
None of the ingredients is listed.	
\cdot NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
· Canada	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
100-51-6 Benzyl alcohol	
98-54-4 4-tert-butylphenol	
25620-58-0 trimethylhexane-1,6-diamine	
1477-55-0 m-phenylenebis(methylamine)	
25154-52-3 nonylphenol	(Contd. on page

Printing date 17.07.2013

Revision: 17.07.2013

(Contd. of page 13)

Trade name: RockSolid Floors Industrial Polycuramine Part B

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

25154-52-3 nonylphenol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

R20/22 Harmful by inhalation and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

- R22 Harmful if swallowed.
- R34 Causes burns.

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R63 Possible risk of harm to the unborn child.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 15)

Printing date 17.07.2013

Revision: 17.07.2013

Trade name: RockSolid Floors Industrial Polycuramine Part B

(Contd. of page 14)

HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent • **Sources** SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com