
ROCKSOLID FLOORS CONSTANT CLEAN

Product Description

ROCKSOLID CONSTANT CLEAN is the most advanced commercial cleaning product on the market today. Using safe, naturally occurring microorganisms rather than harsh chemicals, CONSTANT CLEAN breaks down grease, fats, oils, dirt, grime and many other contaminants into harmless bioproducts (H₂O and CO₂). It also removes trapped oils that cause stains, produce nasty odors and make surfaces slippery. Best of all, it's biodegradable and near pH- neutral

Product Features

- ❖ Revolutionary NEW cleaning product
- ❖ Never stops working
- ❖ Breaks down contaminants
- ❖ Indoor & Outdoor use
- ❖ Naturally Occurring Microbes
- ❖ Works great for old stains
- ❖ Always working, even when you're not
- ❖ Consumes contaminants until they are gone
- ❖ Eco Safe
- ❖ Easy to use
- ❖ Once a cleaning pattern is established, cleaning frequency can often be reduced
- ❖ Reduces slippery conditions, even when wet.

Temperature

Apply when outside temperatures are between 40 – 90 degrees Fahrenheit.

Primary Applications

- ❖ Tile
- ❖ Concrete
- ❖ Floor surfaces
- ❖ Restaurant
- ❖ Food handling facility floors
- ❖ Composite floor cleaning
- ❖ Drains
- ❖ Grease traps
- ❖ Dumpster areas

Application Process

- ❖ Fill clean mop bucket with warm water to desired level. **DO NOT USE HOT WATER!**
- ❖ Pour or dispense 2 oz of Constant Clean per gallon of water
- ❖ Mop floors as usual
- ❖ When water becomes too dirty to use: Empty bucket into drains leading to grease trap
- ❖ Empty bucket onto concrete areas around dumpsters or grease trap

Surface Preparation

Proper surface preparation is crucial to achieving a successful application. Remove all dust, waxes, sealers, old adhesive residue, curing compounds, oils, surface hardeners, paints, old floorings and other loose or foreign material prior to application. For best results, any concrete surface to be treated shall be cured for a minimum of 14 days and free of surface imperfections such as efflorescence. Loose chunks or chips of concrete should be cleared and remove any resulting dust. Smooth, steel troweled surfaces shall be roughened using mechanical means such as shot-blasting, diamond grinding, or water blasting to provide a porous substrate for penetration.

Precautions

Protect glass, aluminum, wood and painted finishes from overspray.

Warranty

The technical data and any other printed information furnished by ROCKSOLID are true and accurate to the best of our knowledge. **ROCKSOLID Constant Clean** conforms to in house quality control procedures and should be considered free of defects. The data provided is believed to be reliable and is offered solely for evaluation. The use of this product is beyond the control of the seller, therefore the buyer assumes all risks of use and handling whether done in a matter that is in accordance with the provided posted directions or not. Rocksolid makes no warranty; expressed or implied, of its products and shall not be liable for indirect or consequential damage in any event.

Shelf Life and Storage

Twelve months in factory delivered unopened buckets. Keep away from extreme heat, cold and moisture. Maintain at a proper storage

temperature of 40-90° F. Keep out of direct sunlight.