

ROCKSOLID FLOORS OIL DESTROYER

Product Description

ROCKSOLID OIL DESTROYER is a heavy duty stripper and degreaser developed from citrus oranges. It's VOC compliant, easy to work with and has a pleasant orange smell. RockSolid Oil Destroyer is excellent for degreasing, stripping, and general cleaning purposes.

Eric Spanier 9/25/13 2:02 PM

Formatted: Font:Agency FB, 10 pt, Not Bold

Eric Spanier 9/25/13 2:02 PM

Formatted: Font:Agency FB, 10 pt, Not Bold

Product Features

- ❖ Low Odor
- ❖ VOC compliant
- ❖ Non-Toxic
- ❖ Biodegradable
- ❖ Pleasant Orange smell
- ❖ Safe to use on delicate surfaces
- ❖ Starts working immediately
- ❖ Use with all of our concrete coatings
- ❖ Use the word degreaser

surface imperfections such as efflorescence. Loose chunks or chips of

Temperature

Apply when outside temperatures are between 40 – 90 degrees Fahrenheit.

concrete should be cleared and remove any resulting dust. Smooth, steel troweled surfaces shall be roughened using mechanical means such as shot-blasting, diamond grinding, or water blasting to provide a porous substrate for penetration.

Primary Applications

- ❖ Garage Floors
- ❖ Bathrooms
- ❖ Multi-purpose cleaner
- ❖ Many other uses

Precautions

Protect glass, aluminum, wood and painted finishes from overspray.

Application Process

- ❖ Apply RockSolid Oil Destroyer to the entire floor.
- ❖ Allow RockSolid Oil Destroyer to soak into the surface for 20 minutes. (longer soak times may be necessary for removal of curing compounds).
- ❖ Work it in with a stiff broom or floor buffer.
- ❖ After scrubbing the floor, rinse thoroughly with water. Vacuum or squeegee dry the entire floor.
- ❖ Re-application may be necessary for extremely dirty, stained floors, or hard-to-remove.

Warranty

The technical data and any other printed information furnished by ROCKSOLID are true and accurate to the best of our knowledge. **ROCKSOLID Oil Destroyer** conforms to in house quality control procedures and should be considered free of defects. The data provided is believed to be reliable and is offered solely for evaluation. The use of this product is beyond the control of the seller, therefore the buyer assumes all risks of use and handling whether done in a matter that is in accordance with the provided posted directions or not. ROCKSOLID makes no warranty; expressed or implied, of its products and shall not be liable for indirect or consequential damage in any event.

Eric Spanier 9/25/13 11:28 AM

Deleted: (swing - scrubber).

Eric Spanier 9/25/13 11:28 AM

Formatted: Font:Agency FB, 10 pt

Surface Preparation

Proper surface preparation is crucial to achieving a successful application. Remove all dust, waxes, sealers, old adhesive residue, curing compounds, oils, surface hardeners, paints, old floorings and other loose or foreign material prior to application. For best results, any concrete surface to be treated shall be cured for a minimum of 14 days and free of

Shelf Life and Storage

Twelve months in factory delivered unopened buckets. Keep away from extreme heat, cold and moisture. Maintain at a proper storage temperature of 40-90° F. Keep out of direct sunlight.

Coverage

Expected coverage is 200sqft per Gallon