
ROCKSOLID WOOD STRIPPER

Product Description

ROCKSOLID WOOD STRIPPER quickly cuts through and removes old, weathered coatings including stains, tinted water repellants or other transparent finishes with ease. Oil base, water base, and tough to remove latex stains are easily removed as well. Once stripped, wood is restored to its bright, clean, and natural look.

Product Benefits

- ❖ Strips old wood
- ❖ Cleans
- ❖ Restores
- ❖ Removes Dirt
- ❖ Prepares Wood for a new finish
- ❖ Works in Minutes
- ❖ Non-flammable
- ❖ Bio-degradable
- ❖ VOC compliant
- ❖ Water based

Primary Applications

- ❖ Decks
- ❖ Wood Docks
- ❖ Outdoor wood furniture
- ❖ Wood Fences

Temperature

50°F - 100°F (10°C - 38°C)

Keep Product From Freezing- Do not store in Temperatures lower than 50 F.

Shelf Life and Storage

Twelve months in factory delivered unopened buckets. Keep away from extreme heat, cold and moisture. Maintain at a proper storage temperature of 40-90° F. Keep out of direct sunlight.

Surface Preparation

Sweep away surface dirt and debris. If the surface is in direct sunlight and hot to the touch, dampen with fresh water to cool. Remove any standing water before beginning application.

Application Information

- ❖ Ensure Deck in dry, this product works bests in direct sunlight
- ❖ Liberally work small area at a time by pouring/brushing/ spraying onto deck.
- ❖ Allow it to settle in, keep moist with stripper
- ❖ After 10-15 minutes begin scrubbing with stiff bristled brush.
- ❖ Rinse with power-sprayer or garden hose on its highest pressure setting.
- ❖ If required, repeat above steps

Precautions

Keep out of reach of children and animals. Do not take internally. May be harmful if swallowed. Causes eye and skin irritation. Prevent contact with eye and skin. Wear rubber or PVC gloves and safety goggles during application.

Warranty

The technical data and any other printed information furnished by ROCKSOLID are true and accurate to the best of our knowledge. **ROCKSOLID Wood Stripper** conforms to in house quality control procedures and should be considered free of defects. The data provided is believed to be reliable and is offered solely for evaluation. The use of this product is beyond the control of the seller, therefore the buyer assumes all risks of use and handling whether done in a matter that is in accordance with the provided posted directions or not. ROCKSOLID makes no warranty; expressed or implied, of its products and shall not be liable for indirect or consequential damage in any event.

Coverage Rate

1 Gallon of Solution covers approximately
150sqft

Clean Up

Clean tools and equipment immediately after
use with soap and water.